



Haven Automatic Fire Suppressor

Manufacturer's Specification Sheet

Model: HFS-155

The Haven HFS-155 Automatic Fire Suppressor is a ceiling-mounted, heat-activated fire suppression unit designed for residential and light commercial applications. Utilizing a UL-listed sprinkler head and ABC dry chemical agent, the unit provides reliable, maintenance-free protection in areas up to 100 sq. ft. The HFS-155 integrates seamlessly with interior spaces, offering discreet yet powerful fire protection.

Key Features

- Automatic Heat Activation – UL-listed sprinkler head activates at 155°F (68°C).
- Coverage – Effective suppression for areas up to 10' x 10' (100 sq. ft.).
- Safe & Reliable – UL-listed ABC dry chemical extinguishing agent.
- Electronic Pressure Switch – Automatically signals when internal pressure drops below 155 psi.
- High Purity Propellant – Charged with compressed dry nitrogen for consistent discharge.
- Durable Build – Aluminum body with lightweight design for easy installation.
- Low Maintenance – Self-contained unit, no external piping, power, or wiring required.

Technical Specifications

Specification	Detail
Model	HFS-155
Extinguishing Agent	UL-Listed ABC Dry Chemical
Capacity	5 lb
Coverage Range	10' x 10' (100 sq. ft.)
Activation Temperature	155°F (68°C)
Activation Method	UL-listed sprinkler head
Operating Pressure	175 psi
Electronic Pressure Switch	Activates below 155 psi
Propellant	High-purity compressed dry nitrogen
Cylinder Material	Aluminum
Diameter	4 3/8" (111 mm)
Height	16" (406 mm)

Unit Weight	8.6 lb (3.9 kg)
Ship Weight	11 lb (5.0 kg)
Gross Charged Weight	9.2 lb (4.2 kg)
Safety Data Sheet (SDS)	Click Here for Haven SDS

Ordering Information

Model: HFS-155

SKU: HAV-HFS-155

Package Includes: Fire suppressor, mounting hardware, installation instructions

Warranty: 5-Year Manufacturer's Warranty

Manufacturer Contact

Haven Fire Safety

14 53rd Street, Unit 707

Info@havenfiresafety.com

www.Havenfiresafety.com

